LEICA SILVERLINE 42 mm

Technical Data

Binocular	LEICA SILVERLINE 10 x 42	LEICA SILVERLINE 8 x 42
Order No. Product	40 654	40 653
Delivery scope	Leather carrying strap, contoured, eyepiece cover, case	Leather carrying strap, contoured, eyepiece cover, case
Magnification	10 x	8 x
Front lens diameter	42 mm	42 mm
Exit pupil	4.2 mm	5.2 mm
Twilight factor	20.5	18.3
Field of view at 1,000 m	112 m	130 m
Field of view at 1,000 yds	336 ft	389 ft
Eye-relief	16 mm	15.5 mm
Objective angle of view	6.4°	7.4°
Close focusing distance	approx. 2.9 m/9.5 ft	approx. 3 m/9.8 ft
Diopter compensation	± 4 diopters	± 4 diopters
Automatic diopter compensation ADC™	yes	yes
Eyepieces for eyeglass wearers	yes, removable, with two click stops	yes, removable, with two click stops
Adjustable interpupillary distance	55–75 mm	55–75 mm
Focusing	Internal focusing via central focusing device	Internal focusing via central focusing device
No. of lens elements (each side)	9, all with HDC™ coating	9, all with HDC™ coating
Prism system	Roof prism with phase correcting coating P40 and HighLux-System HLS™	Roof prism with phase correcting coating P40 and HighLux-System HLS™
Coating	AquaDura™ coating on outer lens (not on close focus lens)	AquaDura™ coating on outer lens (not on close focus lens)
Watertightness	Watertight to a depth of 5 m/16.5 ft	Watertight to a depth of 5 m/16.5 ft
Housing	Die-cast magnesium, nitrogen-filled	Die-cast magnesium, nitrogen-filled
Dimensions (W x H x D)	120 x 146 x 62 mm 4¾ x 5¾ x 2½ in	121 x 141 x 63 mm 4¾ x 5⅝ x 2½ in
Weight	approx. 695 g / 24.7 oz	approx. 710 g / 25 oz
Order No. Accessories		
Floating carrying strap, orange	42 163	42 163
Tripod adapter	42 220	42 220

New: blog Leica-Camera

http://blog.leica-camera.com

Info:

http://de.leica-camera.com/sport_optics/silverline/

Leica Camera AG / Oskar-Barnack-Straße 11 / D-35606 Solms / Telephone +49 (0) 6442-208-0 / Telefax +49 (0) 6442-208-333 / info@leica-camera.com / www.leica-camera.com